

OleumTech®



Best-in-Class Instrumentation Solutions



OleumTech®

Headquarters
19762 Pauling
Foothill Ranch, CA 92610
oleumtech.com
sales@oleumtech.com
Toll-Free (866) 508-8586

Midland, Texas
6415 N State HWY 349, STE 15
Midland, TX 79705
oleumtech.com
sales@oleumtech.com
Toll-Free (866) 508-8586

Innovative Solutions for Your Most Challenging Applications

Smart Pressure Transmitter DP Transmitter MVS Transmitter RTD Transmitter Flow Totalizers H2S Level Switches Tuning Fork Switches



5-10,000 PSI
1-5 V, 4-20 mA, 4-20 mA/HART
RS485 Modbus



1-5 V, 4-20 mA
4-20 mA/HART
RS485 Modbus



Differential Pressure
Static Pressure
Temperature



PT100 ohm
4-20 mA/HART
RS485 Modbus



RS485 Modbus & Local Read Options
Works with 3rd-party Turbine Flow Meters



0.0 to 200.0 ppm
Replaceable Sensor Module
2 Alarm Status DOs (SSR)



Top and Side Mount Options
Single or Dual Actuation Options



2"-4" and 5"-118" Length Options
316 or 316L SS

Coriolis Flow Meters



Superior Measurement Accuracy
0.5, 1, 1.5, 2, 3 and 4-inch Tube Sizes
RS485 Modbus, 4-20 mA, 0-10 KHz Pulse Output

Electromagnetic Flow Meter



Remote and Direct Mount Options
RS485 Modbus, 4-20 mA, 2-8 KHz Pulse Output
0.5 to 12-inch Tube Sizes

Guided Wave Radar



Up to 600 Inches / 15 Meters
316L SS or PFA-Coated Cable Options
RS485 Modbus + 4-20mA or
4-20mA/HART Output Options

Thief Hatch Switch



30 ft. Robust Outdoor Cable
Mount on Either Side of Thief Hatch
Simple Apparatus / Dry Contact Switch (SPST)

Level - Resistive



Product, Interface, Temp.
DI Option Available

RS485 Modbus & 4-20 mA/HART
Options Available

Flexible Sensor - PTFE
8 - 38 ft Lengths



Rigid Sensor - 316 SS
2 - 26 ft Lengths